

# Xerox<sup>®</sup> WorkCentre<sup>®</sup> 7830/7835/ 7845/7855 Color Multifunction Printer

The WorkCentre 7800 Series Color Multifunction Printer is built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to **www.connectkey.com**.

	High Capa Stapler and Work Surface	ay Option	Finisher With Booklet Maker Professiona	al Finisher
System Specifications	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
<b>Speed</b> Color / Black-and-white	Up to 30 / 30 ppm	Up to 35 / 35 ppm	Up to 45 / 45 ppm	Up to 50 / 55 ppm
Monthly Duty Cycle <sup>1</sup>	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages
Recommended Average Monthly Print Volume <sup>2</sup>	8,000 to 12,000 pages	10,000 to 15,000 pages	16,000 to 20,000 pages	18,000 to 22,000 pages
Hard Drive / Processor / Memory	Minimum 160 GB / 1.2 GHz Dual-core	/ 2 GB system plus 1 GB page memor	/	
Connectivity	10/100/1000Base-T Ethernet, High-Spe	eed USB 2.0 Direct Print, Optional Wi-Fi (	with Xerox® USB Wireless Adapter)	
Controller Features	Unified Address Book, Remote Control P	Panel, Online Support (accessed from the	user interface and print driver), Configura	tion Cloning
Optional Controller	EFI Server			
Copy and Print				
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 2400 dpi			
First-print-out Time Color / Black-and-white	As fast as 9 / 7.7 seconds		As fast as 7.5 / 6.4 seconds	As fast as 7.1 / 5.9 seconds
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)			
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Color By Words			
Mobile Printing	Apple® AirPrint™, Xerox® PrintBack, Xerox® Mobile Print Solution (Optional), Xerox® Mobile Print Cloud (Optional), Mopria™ certified			
Scan				
Standard Features	Destinations: Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearized PDF / PDF/A			
Optional Features	Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Business Innovation Partners			
Fax				
Standard Features	Internet Fax, Fax Build Job, Network S	erver Fax Enablement		
Optional Features	Fax Forward to Email or SMB, Walk-up	Fax (one-line and two-line options, inc	ludes LAN Fax)	
Security				
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) (undergoing evaluation), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions			
Optional Features	McAfee Integrity Control, Xerox Secure	e Access Unified ID System®, Smart Ca	rd Enablement Kit (CAC/PIV/.NET)	
Accounting				
Standard Features	5. 15.	int, Scan, Fax, Email), Network Account	5	
Optional Features	Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Business Innovation Partners			

Device Specifications					
Control Panel Languages	US English, International English, Inte Finnish, Turkish, Greek, Russian, Czech		, International Spanish, Dutch, Brazilian Po talan	rtuguese, Swedish, Norwegian, Danish,	
Accessories					
Optional	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Integrated Office Finisher (optional with 7830/7835 only) Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Professional Finisher Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® EFI Fiery® Network Controller Walk up Fax (One- or Two-line options, includes LAN Fax) Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit				
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device	e, this is an interface to third party	access control devices, such as coin mach	ines and card readers.	
Electrical Requirements					
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A				
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 10 A				
Power Consumption	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855	
Running (Average)	110V: 641 watts 220V: 643 watts	110V: 673 watts 220V: 691 watts	110V: 750 watts 220V: 764 watts	110V: 828 watts 220V: 862 watts	
Standby Mode	110V and 220V: 62 watts		110V: 98.6 watts 220V: 95.9 watts	110V: 85.7 watts 220V: 121 watts	
Low Power Mode	110V and 220V: 59 watts		110V and 220V: 80.5 watts	110V: 80 watts 220V: 94.6 watts	
Auto Off / Sleep mode	110V: 4.2 watts     110V: 4.3 watts       220V: 4.8 watts     220V: 4.8 watts       (Default time to Sleep mode = 2 mins)     (Default time to Sleep mode = 2 mins)			nins)	
Warm-up (from Off)	As fast as 194 seconds (Dependent o	n number of services registered)			
Low Power Recovery	< 9 seconds				
Operating Environment					
Required Temperature Range	50° to 82° F (10° to 28° C)				
Required Relative Humidity	15% to 85%				
Sound Power Levels Operating Standby	6.5 LwAd (B) 3.5 LwAd (B)	6.5 LwAd (B) 3.4 LwAd (B)	6.6 LwAd (B) 3.6 LwAd (B)	6.8 LwAd (B) 3.6 LwAd (B)	
Sound Pressure Levels Operating Standby	54 LpAd (dBA) 16.5 LpAd (dBA)	54.3 LpAd (dBA) 16.5 LpAd (dBA)	55.7 LpAd (dBA) 18.5 LpAd (dBA)	55.8 LpAd (dBA) 18.5 LpAd (dBA)	
Dimensions and Weight	Width	Depth	Height	Weight	
Base Configuration	25.2 in. / 640 mm	27.5 in. / 699 mm	45.2 in. / 1,149.2 mm	334.2 lbs. / 151.9 kg	
With Integrated Office Finisher (7830/7835 only)	44.4 in. / 1,129 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	348 lbs. / 158 kg	
With Office Finisher LX (with Booklet Maker)	65.6 in. / 1,666 mm	27.9 in. / 709 mm	45.2 in. / 1,149 mm	403 lbs. / 183 kg	
With Professional Finisher	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	526 lbs. / 239 kg	
With Professional Finisher and High Capacity Feeder	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	590 lbs. / 268 kg	

Certifications						
	FCC Class A Compliant (US), ICES Class A Compliant (Canada)         CSA Listed (UL 60950-1, Second Edition)         CB Certified (IEC 60950-1, Second Edition)         GS Mark         ENERGY STAR® 2.0         EPEAT (United States)         GOST         NOM         Blue Angel         Environmental Choice         CE Mark         Common Criteria (IEEE 2600.2 standard)         Citrix® Certified         WHQL         IPv6 Ready         Cerner         MEDITECH         SAP         To view the latest list of certifications, go to www.xerox.com/OfficeCe	ertifications.				
Paper Handling	WorkCentre 7830 WorkCentre 7835	WorkCentre 7845	WorkCentre 7855			
Duplex Automatic Document	Feeder					
Capacity <sup>3</sup>	110 sheets	130 sheets (Single-pass DADF	)			
Speed	up to 70 image per minute black-and-white and color (simplex)					
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. / A5 to A3	5.5 x 8.5 in. to 11 x 17 in. / A5 to A3				
Weights	16 lb. bond to 32 lb. bond / 50 gsm to 128 gsm					
Bypass Tray						
Capacity <sup>3</sup>	100 sheets					
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in. / 89 x 98 mm to 320 x 483 r	mm				
Weights	16 lb. bond to 110 lb. cover / 55 to 300 gsm	16 lb. bond to 110 lb. cover / 55 to 300 gsm				
Types	BondCard StockCard Stock ReloadedCustomEnvelopesGlossy Card StockGlossy Card Stock ReloadedHeavyweight Card StockHeavyweight Glossy Card Stock ReloadedHeavyweight Glossy Card Stock ReloadedHeavyweight Glossy Card Stock ReloadedHeavyweight Glossy Card Stock ReloadedHeavyweight Glossy Card Stock ReloadedLabelsLetterheadLightweightLightweight Card Stock ReloadedLightweight Glossy Card StockLightweight Glossy Card StockLightweight Glossy Card StockLightweight Glossy Card StockLightweight Glossy Card Stock ReloadedPlain ReloadedPreprintedRecycledTransparencies					
3 Tray Module (Total 2,180 sh	eets) (Optional with WorkCentre 7830/7835 only)					
Capacity <sup>3</sup>	Trays 1-4: 520 sheets each					
Sizes	Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x Trays 2-4: Custom Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 139.					
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm					

Туреѕ	Bond
	Card Stock
	Card Stock Reloaded Custom
	Glossy Card Stock
	Glossy Card Stock Reloaded
	Heavyweight Card Stock
	Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock
	Heavyweight Glossy Card Stock Reloaded
	Hole punched
	Labels
	Letterhead Lightweight
	Lightweight Card Stock
	Lightweight Card Stock Reloaded
	Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded
	Plain
	Plain Reloaded
	Preprinted
	Recycled Transparencies
High Capacity Tandem Tray (Total	3,140 sheets) (Available with all configurations)
Capacity <sup>3</sup>	Tray 1: 520 sheets Tray 2: 520 sheets
	Tray 3: 867 sheets
	Tray 4: 1,133 sheets
Sizes	Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm
	Tray 2: Custom Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 140 x 182 mm to 320 x 458 mm
	Trays 3-4: Standard Sizes: 8.5 x 11 in. LEF / A4, JIS B5, Executive (7.25 x 10.5 in.)
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm
Туреѕ	Bond
	Card Stock Custom
	Glossy Card Stock
	Hole punched
	Labels Letterhead
	Lightweight Card Stock
	Lightweight Glossy Card Stock
	Plain
	Preprinted
High Capacity Feeder (HCF) (Option	
Capacity <sup>3</sup>	2000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. / A4 LEF
Weights	16 lb. bond to 140 lb. index / 55 to 256 gsm
Envelope Tray (Optional - Replaces	Tray 1)
Capacity <sup>3</sup>	Up to 60 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm
Total Capacity	
Device Total Capacity <sup>3</sup>	5,140 sheets
Finishing	
Output Trays (Standard)	
Stacking Trays <sup>3</sup>	Dual Offset Catch Tray – up to 250 sheets each
Stucking mays	Left-side Face up Tray – up to 100 sheets
Integrated Office Finisher (Optiona	al with 7830/7835)
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3
	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm
Sizes	5.5 X 5.9 ID 10 11.7 X 17 ID 7 69 X 96 IDD 10 297 X 452 IDD
Sizes Weights	16 lb. bond to 80 lb. cover / 60 to 256 gsm

Stapling	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)					
Office Finisher LX (Optional)						
Capacity <sup>3</sup>	Stacking Tray: 2,000 sheets unstapled	or 1,000 sheets single stapled or 750 s	heets dual stapled (8.5 x 11 in. / A4)			
Sizes	7.2 x 8.3 in. to 11.7 x 17 in. / 182 x 21	0 mm to 297 x 432 mm				
Weights	16 lb bond to 80 lb cover / 60 to 256	qsm				
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm	<u> </u>				
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch	2-3 Hole Punch				
Booklet Maker for Office Finisher	LX (Score/Crease, Saddle-stitch Staple	) (Optional)				
Capacity <sup>3</sup>	40 booklets (2-15 sheets per booklet -	- 20 lb. / 80 gsm or less)				
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF				
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 g	gsm				
Score / Crease	1-15 sheets / unstapled					
Professional Finisher (Optional)						
Capacity <sup>3</sup>	Stop Tray:           500 sheets of 8.5 x 11 in. / A4 unstapled           Stacking Stapling Tray:           1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or           200 stapled sets of 8.5 x 11 in. / A4 or           100 stapled sets of 11 x 17 in. / A3 / SRA3					
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling					
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm					
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported					
Hole Punch (Standard) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)					
Booklet Maker	Bi-fold up to 5 sheets	Saddle-stitch 2 to 15 sheets (14 sheets of 90 gsm or less plus 1 sheet of 169 gsm) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 supported				
Convenience Stapler (Optional - I	Includes Work Surface)					
Capacity <sup>3</sup>	50-sheet stapling 5,000 staples Requires a separate outlet					
Сору	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855		
First-copy-out Time (Letter/A4-size, from Platen to Center Tray) (Color / Black-and-white)	As fast as 8.4 seconds / As fast as 6.7 seconds	As fast as 8.2 seconds / As fast as 6.8 seconds	As fast as 7.5 seconds / As fast as 6.2 seconds	As fast as 7.1 seconds / As fast as 5.5 seconds		
Sides (input:output)	1-1, 1-2, 2-2, 2-1					
Quantity	1 to 9,999	1 to 9,999				
Resolution (max.)	Up to 600 x 600 dpi	Up to 600 x 600 dpi				
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments					
		Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)				

Copy Features	Annotation and Bates <sup>™</sup> stamping (with color capability and font size adjustment)         Authentication for Services (i.e. Color Copy)         Auto Paper Select         Auto Reduction & Enlargement to fit selected paper size         Auto Tray Switching         Automatic 2-sided/Duplex         Booklet Creation         Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built)         Collation         Covers (Front only, front and back, back only, printed inside and out: Blank or Printed)         Dividers (blank)         Edge Erase         Features Help (Intuitive text and graphic descriptions)         ID Card Copy         Image Quality Adjustments         Image Quality Adjustments         Image (negative or mirror image)         Large Job Interrupt         Multi-up (up to 15 columns by 15 rows)         Sample Set         Save Job Settings         Single Color         Stapling         Transparencies
Xerox® Copier Assistant®	Narsparences         Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com
Print	WorkCentre 7830 WorkCentre 7835 WorkCentre 7845 WorkCentre 7855
Print Resolution	Up to 1200 x 2400 dpi
Print Feαtures	Application DefaultsBanner Sheet Enable / DisableBi-directional StatusCustom Color Options (Color By Words)Cover SelectionDelay Print (specific time)User PermissionsImage Options (Toner Saver, Resolution (Standard, Enhanced, High)Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size)OverlaysPaper Selection by AttributeLAN Fax (requires optional Fax Kit)Sample SetSaved Job (color jobs can be printed as monochrome)Secure Print with Timed DeletionSpecial Pages (exception page programming: covers, inserts, exception pages)Store and Recall Driver SettingsSustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS <sup>«</sup> , PCL Color jobs can be printed as monochrome
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64

Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD         NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)         AppleTalk®: EtherTalk®         Microsoft Windows Networking over IP         Bonjour®         IPv6         Secure FTP         Most protocols not in use can be disabled			
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP	, DNS, SSDP		
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts			
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox <sup>®</sup> and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and m consistent, easy-to-use interface for end-users, reducing the number of suppo			
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print device single driver. The Xerox® Pull Print Driver extends convenience across a broad configure multiple drivers. Used in conjunction with Xerox Secure Access Unif	range of printing assets. IT administrators no longer need to manage and		
Print Solutions				
Xerox® Mobile Print Cloud (Optional)	Xerox <sup>®</sup> Mobile Print Cloud addresses the needs of businesses with a mobile w burdening staff, budget or infrastructure. Getting started takes only a few mi printer. Accurate printing with true Microsoft <sup>®</sup> Office <sup>®</sup> rendering and more. Pr	nutes via the cloud. Print from any mobile device to nearly any brand of		
Xerox® Mobile Print Solution (Optional)	Xerox <sup>®</sup> Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox <sup>®</sup> Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.			
Unified Address Book for Fax, Int	ernet Fax, Email and Scan to			
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of fax numbers, emails, etc.			
Scan	WorkCentre 7830 WorkCentre 7835	WorkCentre 7845 WorkCentre 7855		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to ne concurrent jobs)	etwork or fax jobs (priority is for return of scanned originals and printing		
Input Speed	Scan at up to 70 ipm color scanning, up to 70 ipm black-and-white – $8.5\ x$ 11 in. / A4 LEF	Scan at up to 133 ipm color scanning, up to 133 ipm black-and-white – 8.5 x 11 in. / A4 LEF		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)			
Maximum Scan Area	11 x 17 in. / A3			
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to Confirmation sheet options	o other MFPs		
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS			
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A			
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templat name, default value and other configurations	es and unlimited fields within the template – Metadata field consists of field		
	Customized fields viewed on user interface for variable data input			

Scan to Email (Standard)			
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options     Scan to Email S/MIME Encryption     Email Signing (requires Smart Card option)     Auto send to self		
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilizes the Unified Address Book		
Scan to (Standard)			
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)		
Network Scanning – Software Sol	utions		
Xerox® Scan to PC Desktop® Professional (Optional)	<ul> <li>A desktop offering that provides advanced document imaging, archiving, editing and organization tools:</li> <li>PaperPort Professional image viewing and file management software <ul> <li>Complete PDF functionality</li> <li>Secure PDF workflow of all scanning applications</li> </ul> </li> <li>OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion</li> <li>Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability</li> </ul>		
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.		
Xerox® ConnectKey® Share to Cloud (Optional)	ConnectKey Share to Cloud provides organizations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.		
Xerox <sup>®</sup> ConnectKey <sup>®</sup> for	Xerox <sup>®</sup> ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise		
DocuShare® (optional)	document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).		
Security			
Features	<ul> <li>Expanded Authentication <ul> <li>Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB</li> <li>(Windows Server 2003 / Windows Server 2008), NDS, LDAP</li> <li>Xerox Secure Access Unified ID System<sup>®</sup></li> <li>Local Authentication (internal database)</li> <li>Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) /.NET</li> </ul> </li> <li>Secure Data <ul> <li>Digitally signed PDF (when using Smart Card authentication)</li> <li>Encrypted Scan to Email</li> <li>Encrypted Password Protected PDF (when using Email and Network Scan Templates only)</li> <li>Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>Immediate Image Overwrite</li> <li>On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>FIPS 140-2 256 bit Hard Disk Encryption</li> <li>Expanded Authorization</li> <li>Sa access based on network credentials</li> <li>Authorization per user per service</li> <li>User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver</li> <li>Secure Network Access</li> <li>IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPs, 802.1X, Cisco<sup>®</sup> TrustSec Identity Services Engine (ISE) integration, Device Security</li> <li>McAfee<sup>®</sup> Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional)</li> <li>Common Criteria Certification ISO 15408</li> </ul> </li> </ul>		
System® (Optional)	Aerox secure Access United ID system integrates your Xerox <sup></sup> multifunction printers with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions		
Fax			
Network Server Fax Features			
Compatibility	ITU (CCITT) group 3 Various Xerox Business Innovation Partner Solutions		
Maximum Scan Area	11 x 17 in. / A3		
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum)		
	Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)		

Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi		
Internet Fax Features	Standard. 200 x 100 dpi		
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP)		
cupublicy	Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients		
Directory Access	Utilizes the Unified Address Book		
Send / Receive	Multi-page TIFF, Image only PDF		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)		
Network Protocols	SMTP (send), POP3 (receive)		
Compliance	ITU-T T.37 compliant		
Walk-up Fax Features (Optional	(Customer-installable) – 1 and 2 lines)		
Compatibility	ITU (CCITT) Group 3		
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilizing T38 (optional)		
Compression / Speed	MH/G3, MMR/SG3		
Resolution	Walkup Send:Standard: 200 x 100 dpiFine: 200 x 200 dpiSuperfine: 600 x 600 dpiReceive:Accepts all sizes		
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)		
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay		
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only		
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report		
Directory Access	Utilizes the Unified Address Book Group fax available		
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals		
Auto Resend	Up to 5 attempts		
Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2		
Xerox® CentreWare® Web	<ul> <li>A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:</li> <li>Works with any SNMP-managed printer from any manufacturer.</li> <li>Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher.</li> <li>CentreWare Integration available for Tivoli<sup>®</sup> NetView<sup>®</sup>, Unicenter TNG<sup>®</sup>, Microsoft Management Console (MMC), HP<sup>®</sup> OpenView<sup>®</sup></li> </ul>		
Novell NDPS/NEPS	Server gateway application: centralized management tool.		

Xerox® Device Manager	<ul> <li>Xerox<sup>®</sup> Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox<sup>®</sup> Device Manager provides:</li> <li>Device monitoring and troubleshooting</li> <li>Extensive reporting and discovery of new devices</li> <li>Usage collection, chargeback and billing capabilities</li> </ul>		
Xerox <sup>®</sup> Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions		
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions		
CentreWare Internet Services – Int	tegrated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller:		
	Tray status/contents     Consumables status     Alerts     Remote Control Panel		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS <sup>4</sup> , TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese		
Remote Services			
Xerox <sup>®</sup> MeterAssistant <sup>®</sup>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
Accounting			
Xerox® Standard Accounting (Stan	dard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>		
Accounting Options – Network Acc	counting – Third Party Enablement		
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>		
EFI Fiery Network Controller (Option	onal)		
Processor	2.9 GHz, Intel® Pentium® G850 Dual-Core		
Memory (ESS)	1 GB		
System Disk	500 GB HDD		
Print Languages (PDL)	PostScript v 3019		

Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Color Tables Expert Color Settings: Profile, Rendering and Simulation FreeForm – Variable Data capabilities Booklet Maker 4.0 – booklet wizard to create booklets Print from USB flash drive Paper Catalog Secure Erase EFI PrintMe Fiery® VUE					
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet					
Optional	Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtual Print) Network Switch to connect both printer and Fiery Controller to Network	Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtual Print)				
Supplies						
Toner Cartridges (Metered)⁵	Black	26,000 pages	006R01509			
	Cyan	15,000 pages	006R01512			
	Magenta	15,000 pages	006R01511			
	Yellow	15,000 pages	006R01510			
Toner Cartridges (Sold) <sup>5</sup>	Black	26,000 pages	006R01513			
	Cyan	15,000 pages	006R01516			
	Magenta	15,000 pages	006R01515			
	Yellow	15,000 pages	006R01514			
Transfer Belt Cleaner	1 Assembly	160,000 pages	001R00613			
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13064			
Staple Cartridges	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964			
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897			
	for Professional Finisher Booklet Maker (4 cartridges per carton)	5,000 each cartridge	008R12925			
Staple Refills	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)       5,000 each refill       008R12941					
Xerox <sup>®</sup> Smart Kit <sup>®</sup>						
Drum Cartridge <sup>6</sup>	1 Cartridge per Color	125,000	013R00662			
Waste Toner Container <sup>7</sup>	1 Cartridge	43,000	008R13061			

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> XPS option is required to print XPS files.

<sup>5</sup> Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality setpoints.

<sup>6</sup> Average drum yield is based on a run length of 5 pages of 8.5 x 11 in. / A4 LEF pages, with split of 30% color / 70% black-and-white pages.

<sup>7</sup> Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, call 1-800-ASK-XEROX or visit us at www.xerox.com/office



©2014 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey®, Copier Assistant®, DocuShare®, Global Print Driver®, MeterAssistant®, Mobile Express Driver®, Scan to PC Desktop®, SmartKit®, SupplesAssistant®, WorkCentre® and Xerox Secure Access Unified ID System® are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR® undellines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 10/14 BR9497 W78SS-01UH